

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/034056 A2

(51) International Patent Classification⁷: G01N 33/50

(21) International Application Number:

PCT/US2003/031859

(22) International Filing Date: 8 October 2003 (08.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/416,676 8 October 2002 (08.10.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: NYLESE, Tara [US/US]; 819 Chestnut Court, Marco Island, FL 34145 (US).


(74) Agents: BEUSSE, James, H. et al.; Beusse Brownlee Bowdoin & Wolter, P.A., 390 N. Orange Avenue, Suite 2500, Orlando, FL 32801 (US).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PORTABLE DIAGNOSTIC DEVICE AND METHOD FOR DETERMINING TEMPORAL VARIATIONS IN CONCENTRATIONS



(57) **Abstract:** A rapid assay concentration device. In one form, the device includes a substrate and a plurality of elongated membranes on the substrate. At least one capture zone is formed in each membrane. Each capture zone is responsive to the presence of a target chemical in the fluid. Capture zones on different membranes have different threshold levels of response to the chemical. In a method for monitoring temporal changes of analyte levels in a source multiple test devices are provided, with each device including a plurality of regions. Each region is responsive at a different sensitivity level to indicate presence of the analyte. A source sample is brought into contact with a first of the test devices to determine whether the source contains a level of analyte sufficient to induce a response thereto in one or more of the test unit regions. A different sample from the source is brought into contact with a second of the test devices to determine whether the source contains a level of analyte sufficient to induce a response thereto in one or more regions of the second test device.